






■ Dual Row QPL Ordering Guide

Examples:

M32139-03-A-01-S-N Bi-Lobe Male, 9 contacts, 6.0" White 30 AWG wire, Jackscrew, Aluminum shell, Nickel-Plated

M32139-04-A-04-T-N Bi-Lobe Female, 21 contacts, 6.0" Colored AWG wire, Threaded Hole, Aluminum Shell, Nickel-Plated

(Each option separated by a hyphen)

Basic Spec	Series	Slash Number	Wire Type	Hardware	Shell Material and Finish	Space Class
M32139	MNPO	Plugs 03-A - Pin Connector, 9 Contacts Single 03 - B-Pin Connector, 15 Contacts Single 03 - C-Pin Connector, 21 Contacts Single 03 - D-Pin Connector, 25 Contacts Single 03 - E-Pin Connector, 31 Contacts Single 03 - F-Pin Connector, 37 Contacts Single 03 - G-Pin Connector, 51 Contacts Single	NEMA HP-3-ETXBBB Wire (#30Awg,7StrandSilver-Coated Copper,ExtrudedPTFEInsulation, 250 V rms, 200° C.) 01 - 6 inches White 02 - 18 inches White 03 - 36 inches White 04 - 6 inches 10 Color Repeat 05 - 18 inches 10 Color Repeat 06 - 36 inches 10 Color Repeat	S Jackscrew,#0-80,Hex Head(Slash01&03 PinConnectorsOnly)	 C Aluminum Shell, Cadmium Plated	S Space Class (Not For Use With Cadmium Plated Aluminum Shells)
	MNSO	Receptacles 04 - A-Socket Connector, 9 Contacts Single 04 - B-Socket Connector, 15 Contacts Single 04 - C-Socket Connector, 21 Contacts Single 04 - D-Socket Connector, 25 Contacts Single 04 - E-Socket Connector, 31 Contacts Single 04 - F-Socket Connector, 37 Contacts Single 04 - G-Socket Connector, 51 Contacts Single	M22759/33-30 Wire (#30Awg,7StrandSilver-Coated High-StrengthCopper,Extruded Cross-LinkedModifiedETFE Insulation,600Vrms,200°C.) 07 - 6 inches White 08 - 18 inches White 09 - 36 inches White 10 - 6 inches 10 Color Repeat 11 - 18 inches 10 Color Repeat 12 - 36 inches 10 Color Repeat	T Threaded Hole, #0-80 (Slash02&04Socket ConnectorsOnly)	 N Aluminum Shell Electroless Nickel Plated	
			Composite PTFE/ Polyimide Wire (#30Awg,7StrandSilver-Coated High-StrengthCopper,Extruded Cross-LinkedModifiedETFE Insulation,600Vrms,200°C.) 13 - 6 inches White 14 - 18 inches White 15 - 36 inches White 16 - 6 inches 10 Color Repeat 17 - 18 inches 10 Color Repeat 18 - 36 inches 10 Color Repeat	RH RoHS COMPLIANT 	 S Stainless Steel Shell Passivated	
					 T Titanium Shell Unplated	

9

CAGE Code 61873

■ Dual Row

Pre-Wired Dual Row Bi-Lobe® nanos can be ordered with full QPL approval. These assemblies are crimped using proprietary automated crimping systems in Omnetics MIL- STD-790 approved manufacturing facility pre-crimped wires & contacts are potted in place further protecting the integrity of the crimp joint.

- Building these as full QPL parts gives users an added level of confidence for critical applications.

Commercial off the shelf (COTS) non-QPL versions are also available with 18" of color coded 30 AWG Teflon for quick turn around.



These connectors are available in standard sizes ranging from 9 through 65 positions.

■ Electro-Mechanical Specs

■ Durability:	_____	200 Mating Cycles min
■ Temperature:	_____	-55°C to +125 °C (200 °C w/HTE)
■ Current rating:	_____	1 amp per contact
■ Voltage Rating (DWV):	_____	250 VAC RMS Sea Level
■ Insulation Resistance:	_____	5,000 Megohms min
■ Shock:	_____	100 g's discontinuity < 10 nanoseconds
■ Vibration:	_____	20 g's discontinuity < 10 nanoseconds
■ Thermal Vacuum Outgassing:	_____	1.0% max TML, 0.1% max VCM
■ Contact Resistance:	_____	71 mV drop @ 1 amp
■ Mating/Unmating Force:	_____	7 oz. (.198 kg) max per contact

■ Material Specifications

■ Shell Material and Finish:	_____	Aluminum Shell, Electroless Nickel plated Aluminum Shell, Cadmium plated Titanium Shell, Unplated Stainless Steel Shell, Passivated
■ Insulator:	_____	Liquid Crystal Polymer (LCP)
■ Pin:	_____	Gold Plated BeCu
■ Socket:	_____	Gold Plated Copper Alloy
■ Encapsulant:	_____	Epoxy

CAGE Code 61873

■ Bi-Lobe® and MIL-DTL-32139 Specifications

1. Scope: These specifications highlight some of the standard requirements of Omnetics' Bi-Lobe® style nano connectors in both QPL & non-QPL versions. These connectors have contacts densely packed with centerlines of .025" (.64mm) and are commonly used in mission critical applications.

2. Precedence of Requirements: The specifications herein are a select summary of those called out in MIL-DTL-32139. The complete controlled version of MIL-DTL-32139 from DSCC takes precedence over these pages. For non-QPL parts, requirements of customer specifications and Omnetics' detail drawings will take top priority.

3. Quality & Material

3.1. Statistical Process Control (SPC): Omnetics uses statistical process control (SPC) techniques, when possible, in the manufacturing of Bi-Lobe® nano connectors. The SPC program is maintained in accordance with MIL-STD-790. Where SPC cannot be utilized because of non-continuous production, a lot sampling plan for inspection with C = 0 (accept on zero defects) may be utilized. The SPC and C = 0 programs are documented and maintained as part of our overall reliability assurance program, as specified in MIL-STD-790.

3.2. Pin Contact Finish: Pin contacts are gold plated in accordance with ASTM B488, Type II, Code C, class 1.27, 50 micro inches minimum thickness, over 50 micro inches of nickel.

3.3. Socket Contact Finish: Socket contacts are gold plated in accordance with ASTM B488, Type II, Code C, class 1.27, 50 micro inches minimum thickness, over 50 micro inches of nickel.

3.4. Insulator Material: Insulator material for connectors is LCP in accordance with ASTM D5138.

3.5. Shells: Shell options include the following materials:

3.5.1. Aluminum, alloy 6061 per SAE-AMS-QQ-A-200/8, plated as follows:

3.5.1.1. Electroless Nickel plated per SAE-AMS-C-26074, class 3 or 4, grade B.

3.5.1.2. Cadmium plated per SAE-AMS-QQ-P-416, type II, class 1, yellow chromate.

3.5.2. Stainless Steel, 303 in accordance with ASTM A582, passivated per ASTM A967.

3.5.3. Titanium, in accordance with MIL-T-81556 or SAE-AMS-4911.

3.6. Encapsulant: Epoxy shall be used as a potting material to prevent contact removal. A suitable material shall be used to enable the connector to pass all required mechanical, environmental and electrical testing.

3.7. Pigtail Wire: Insulated wire shall be in accordance with SAE-AS22759/33, DSCC drawing 04047 or NEMA HP3 for size 30 AWG. (NOTE: Connectors, which are pre-wired with SAE-AS22759/33 and stored in a sealed environment, could experience corrosion. Omnetics takes this into consideration when packaging and storing connectors using this wire.

CAGE Code 61873

■ Bi-Lobe® and MIL-DTL-32139 Specifications cont...

4. Mechanical Requirements

4.1. Contact Wipe: All contacts have a minimum contact wipe of .015 inch (0.38 mm) prior to the connector halves arriving at their fully mated position.

4.2. Durability: MIL-DTL-32139 requires a minimum of 200 mating cycles per test procedure EIA-364-09. Omnetics easily passes this requirement and has conducted and passed internal testing of over 2,000 mating cycles.

4.3. Contact Retention: Contacts will withstand a 2 lb. (0.9 kg) axial load for a min. of 5 seconds.

4.4. Crimp Tensile Strength: 30 AWG wire will not break or pull from crimp joints with an applied force of less than 1.0 lb. (0.44 kg).

4.5. Contact Engaging and Separation Force: Maximum engagement force is 5.0 ounces (141.7 g.) and minimum separation force is 0.4 ounces (11.3 g.) (when using maximum and minimum ID test sleeves.)

4.6. Connector Mating/unmating Force: Maximum mating and unmating force will be less than or equal to 7 ounces (198.4 g.) times the number of contacts.

4.7. Solderability: Printed circuit tails intended for SMT and Thru-Hole soldering will meet the solderability requirements of MIL-STD-202, Method 208.

5. Electrical Requirements

5.1. Current Capability: Contacts can carry 1.0 amp in continuous operation from -55° C to 125 ° C.

5.2. Dielectric Withstanding Voltage (sea Level): Connectors will show no signs of breakdown or flash over at 250 VAC, rms 60 Hz, per the DWV test of EIA-364-20.

5.3. Dielectric Withstanding Voltage (70,000 Feet): Connectors will show no signs of breakdown or flash over at 100 VAC, rms 60 Hz, per the DWV test of EIA-364-20.

5.4. Insulation Resistance: 5,000 Megohms minimum @ 100 VDC per IAW EIA-364-21

5.5. Contact Resistance: 71 mV drop maximum with a 1 ampere test current in accordance with EIA-364-06 using 30 AWG stranded wire.

5.6. Low Level Contact Resistance: 71 milliohms with a test current of 10 milliamperes maximum in accordance with EIA-364-06.

5.7. Magnetic Permeability: The magnetic permeability will not exceed 2 mu when tested in accordance with EIA-364-54.

■ Bi-Lobe® and MIL-DTL-32139 Specifications cont...

6. Environmental Requirements

6.1. Shock: 100 g's when tested for mechanical shock, mated connectors shall not be damaged, and there shall be no loosening of parts. There shall be no interruptions in the circuit which lasts longer than 10 nanoseconds.

6.2. Vibration: 20 g's when tested for vibration, mated connectors shall not be damaged, and there shall be no loosening of parts. There shall be no interruptions in the circuit which lasts longer than 10 nanoseconds.

6.3. Salt Spray (Corrosion): Mated connectors will show no exposure of base metal due to corrosion which will affect performance after be subjected to the salt spray test of EIA-364-26 condition B. Connectors must withstand 48 hours of salt spray. Following the test all connectors shall meet the specified requirements for low-signal level contact resistance and connector mating and unmating forces.

6.4. Thermal Vacuum Out gassing: These connector assemblies shall have a maximum total mass loss (TML) of 1.0 percent of the original specimen mass, and shall have a maximum volatile condensable material (VCM) content of 0.1 percent of the original specimen mass.

6.5. Fluid Immersion: Connectors will continue to adhere to the mating force requirements set forth by MIL-DTL-32139 after be subjected to a 20 hour immersion in synthetic lubricating oil, 2 hour immersion in Perchloroethylene cleaning solvent and 1 hour immersion in coolant fluid. There will be no degradation of the insulators or encapsulates.

6.6. Material Fungus Resistance: Materials used in the construction of these connectors are fungus inert in accordance with ASTM G21.

6.7. Thermal Shock: Connectors will withstand 5 cycles of thermal shock from -55° C to 125 ° C per EIA-364-32, condition I. There will be no detrimental damage or degradation of the electrical performance.

6.8. Humidity: These connectors will meet all the humidity testing requirements in accordance with EIA-364-31, test condition A (excluding steps 7a & 7b). Post humidity, the connectors will pass a 250 VAC DWV test. Within 1 hour the connectors will pass a 1 megohm insulation resistance test. Following 24 hours, the connectors will pass a 1,000 megohm insulation resistance test.

6.9. Marking Permanency: Any marking on the connector shells of these nano connectors shall meet the requirements of MIL-STD-202, Method 215.

CAGE Code 61873